



SAFETY DATA SHEET FAST INDUSTRIAL THINNER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	FAST INDUSTRIAL THINNER
Product number	TH120
Synonyms; trade names	Thinner No.4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	PC 9a: Coatings and paints, thinners, paint removers.
-----------------	---

1.3. Details of the supplier of the safety data sheet

Supplier	Axalta Coating Systems Huthwaite UK Ltd Blackwell Road Huthwaite Nottinghamshire United Kingdom NG17 2RL Tel: +44 (0)1623 510585
Contact person	info-huthwaite@axaltacs.com

1.4. Emergency telephone number

Emergency telephone	United Kingdom: 01623 528938 (Mon-Thu 0700 - 1600 hrs, Fri 0700 - 1245 hrs).
National emergency telephone number	Republic of Ireland: National Poison Information Centre (Ireland) Tel: 01 809 2566 (8am to 10pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Flam. Liq. 3 - H226
Health hazards	Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304
Environmental hazards	Not Classified

2.2. Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H312+H332 Harmful in contact with skin or if inhaled.
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H304 May be fatal if swallowed and enters airways.

FAST INDUSTRIAL THINNER

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	XYLENE
Supplementary precautionary statements	<p>P233 Keep container tightly closed.</p> <p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P331 Do NOT induce vomiting.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P405 Store locked up.</p>

Other information

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

XYLENE		60-100%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Asp. Tox. 1 - H304		

FAST INDUSTRIAL THINNER

ETHYLBENZENE		10-30%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-0000
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373 Asp. Tox. 1 - H304		Classification (67/548/EEC or 1999/45/EC) F;R11 Xn;R20

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information No data available on the mixture itself.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.
Unsuitable extinguishing media	Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create a fire or explosion hazard.

FAST INDUSTRIAL THINNER

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

For non-emergency personnel No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the area. Eliminate all sources of ignition.

For emergency responders Wear protective clothing as described in Section 8 of this safety data sheet. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

FAST INDUSTRIAL THINNER

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 50 ppm 221 mg/m³

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 100 ppm 442 mg/m³

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

Sk

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 100 ppm 442 mg/m³

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 200 ppm 884 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber; thickness 0.35mm minimum. Fluorinated rubber (Viton); thickness 0.4mm minimum. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Check that the respirator fits tightly and the filter is changed regularly.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Colourless.

FAST INDUSTRIAL THINNER

Odour	Aromatic hydrocarbons.
Odour threshold	Not available.
pH	Not available.
Melting point	Approx -34°C
Initial boiling point and range	Approx 137°C
Flash point	25°C Closed cup.
Evaporation rate	0.77 (butyl acetate = 1)
Evaporation factor	Not available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8% Upper flammable/explosive limit: 7%
Vapour pressure	6.7 hPa @ 20°C
Vapour density	Heavier than air
Relative density	0.86 - 0.88
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	430°C
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity \leq 20.5 mm ² /s.
Explosive properties	Not available.
Oxidising properties	Not available.
<u>9.2. Other information</u>	
Other information	No additional information
Volatile organic compound	This product contains a maximum VOC content of 866 grams per Litre .

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Avoid contact with strong oxidising agents.

10.6. Hazardous decomposition products

FAST INDUSTRIAL THINNER

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 1,240.96

Acute toxicity - inhalation

ATE inhalation (gases ppm) 4,568.99

ATE inhalation (vapours mg/l) 11.17

ATE inhalation (dusts/mists mg/l) 1.52

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Harmful by inhalation. Symptoms following overexposure may include the following: Coughing.

Ingestion

Harmful if swallowed. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach. Adverse symptoms may include the following: Nausea, vomiting.

Skin contact

Harmful in contact with skin. Irritating to skin. Symptoms following overexposure may include the following: Irritation. Redness.

Eye contact

Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

SECTION 12: Ecological information

Ecotoxicity

The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity

No data on the mixture itself. Do not allow to enter drains or watercourses.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient

Not available.

12.4. Mobility in soil

Mobility

No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects

None known.

SECTION 13: Disposal considerations

FAST INDUSTRIAL THINNER

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

FAST INDUSTRIAL THINNER

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UFI	UFI: A2NE-91SA-400Q-83NF
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. 2018 Code of Practice for the Chemical Agents Regulations (HSA Ireland)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	WEL: Workplace Exposure Limit. ATE: Acute Toxicity Estimate. CAS: Chemical Abstracts Service. DMEL: Derived Minimal Effect Level. DNEL: Derived No Effect Level. OELV: Occupational Exposure Limit Value. PNEC: Predicted No Effect Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
Revision date	20/08/2019
Revision	6
Supersedes date	13/04/2018
SDS number	16121

FAST INDUSTRIAL THINNER

Risk phrases in full

R10 Flammable.
R11 Highly flammable.
R20 Harmful by inhalation.
R20/21 Harmful by inhalation and in contact with skin.
R37 Irritating to respiratory system.
R38 Irritating to skin.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure.

The information in this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.