

Resideck Rapid Pourpatch - Filler/Catalyst

Revision 2
Revision date 2019-10-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Resideck Rapid Pourpatch- Filler/Catalyst
--------------	---

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [SU19] Building and construction work; [PC9b] Fillers, putties, plasters, modelling clay;
-------------	---

1.3. Details of the supplier of the safety data sheet

Company	Maker Coating Systems
Address	Unit 5
	Oak Business Units
	Thorverton Road
	Matford Business Park
	Exeter
	EX2 8FS
Web	www.makercoating.com
Telephone	01392 82260
Email	sales@makercoating.com

1.4. Emergency telephone number


Emergency telephone number	01392 822600 Mon - Fri 8am - 5pm / Fri 8am - 3pm
----------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Aquatic Chronic 2: H411;
--------------------------------------	--------------------------

2.2. Label elements

Hazard pictograms	
Hazard Statement	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P273 - Avoid release to the environment.
Precautionary Statement: Response	P391 - Collect spillage.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

Resideck Rapid Pourpatch - Filler/Catalyst

Revision 2

Revision date 2019-10-29

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Triphenyl phosphite	015-105-00-7	101-02-0	202-908-4			Eye Irrit. 2: H319; Skin Irrit. 2: H315; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Aquatic Chronic 2: H411;
diphenyl tolyl phosphate		26444-49-5	247-693-8			Aquatic Chronic 2: H411;
Benzoyl peroxide (Dibenzoyl peroxide)	617-008-00-0	94-36-0	202-327-6			Org. Perox. B: H241; Eye Irrit. 2: H319; Skin Sens. 1: H317;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash off immediately with plenty of soap and water.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation of dust may cause shortness of breath.
Eye contact	May cause irritation to eyes.
Skin contact	No irritation expected.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	No first aid requirements.
Ingestion	If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	No special requirements.
--	--------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	--

Resideck Rapid Pourpatch - Filler/Catalyst

Revision 2

Revision date 2019-10-29

6.4. Reference to other sections

See section 13 for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

7.3. Specific end use(s)

See section 1.2 for further information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Benzoyl peroxide (Dibenzoyl peroxide)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 5
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls



This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace.

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear protective clothing.

Eye / face protection

In case of splashing, wear:.. Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Resideck Rapid Pourpatch - Filler/Catalyst

Revision 2
Revision date 2019-10-29

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Grey
Odour	Slight
Odour threshold	No data available
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic compounds)	0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

	Stable under normal conditions.
--	---------------------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	No Significant Hazard.
--	------------------------

10.4. Conditions to avoid

	No Significant Hazard.
--	------------------------

10.5. Incompatible materials

	Alkalis. Strong acids.
--	------------------------

10.6. Hazardous decomposition products

	Will not decompose if stored and used as recommended.
--	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No Significant Hazard.
-----------------------	------------------------

Resideck Rapid Pourpatch - Filler/Catalyst

Revision 2
Revision date 2019-10-29

11.1. Information on toxicological effects

Skin corrosion/irritation	No Significant Hazard.
Serious eye damage/irritation	May cause irritation to eyes.
Respiratory or skin sensitisation	No sensitization effects reported.
Germ cell mutagenicity	No Significant Hazard.
Carcinogenicity	No Significant Hazard.
Reproductive toxicity	No Significant Hazard.
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	No Significant Hazard.

SECTION 12: Ecological information

12.2. Persistence and degradability

	No data is available on this product.
--	---------------------------------------

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

Partition coefficient

	Resideck Rapid Pourpatch No data available - Filler/Catalyst
--	--

12.4. Mobility in soil

	No data is available on this product.
--	---------------------------------------

12.5. Results of PBT and vPvB assessment

	Not applicable.
--	-----------------

12.6. Other adverse effects

	No data available.
--	--------------------

SECTION 13: Disposal considerations

General information

	01 04 09 waste sand and clays.
--	--------------------------------

Disposal methods

	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
--	--

Disposal of packaging

	Can be sent to landfill if in compliance with local and National regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

Resideck Rapid Pourpatch - Filler/Catalyst

Revision 2
Revision date 2019-10-29

Hazard pictograms



14.1. UN number

UN3077

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains diphenyl phosphate, triphenyl phosphite)

14.3. Transport hazard class(es)

ADR/RID	9
Subsidiary risk	-
IMDG	9
Subsidiary risk	-
IATA	9
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards	Yes
Marine pollutant	Yes

ADR/RID

Hazard ID	90
Tunnel Category	(E)

IMDG

EmS Code F-A S-F

IATA

Packing Instruction (Cargo)	956
Maximum quantity	400 kg
Packing Instruction (Passenger)	956
Maximum quantity	400 kg

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Resideck Rapid Pourpatch - Filler/Catalyst

Revision 2

Revision date 2019-10-29

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

Not required.

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 4 - Eye contact.
Text of Hazard Statements in Section 3	Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Org. Perox. B: H241 - Heating may cause a fire or explosion. Skin Sens. 1: H317 - May cause an allergic skin reaction.
Maximum content of VOC	0 g/l.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.